



Universal form finisher M-781 for outerwear garment

- to be connected with external steam supply



Universal form finisherfor the blowing finishing of all outerwer garments, suitable for laundry, dry-cleaning, manufacturing, pressing and hotel industries.

Finishing cycles controlled by micro-processor

Pneumatic steam control Revolving dummy allows to intervene on the garment even during finishing cycles.

Available extras: Steam Iron Group Steam gun Water spray gun Special dummies.

It is represented by WET Dummy . Best for WET CLEANING system .

It is also available with a stainless steel body.

Technical Characteristics

Required power 400 V./3 + N/50 Hz Fan motor 1HP \div 1,5 HP x MGGV

Air heating electric battery 2 Kw x MGE Steam inlet 1/2 " Return outlet 1/2 " Steam working pressure 7 bar Steam consumption $10 \div 20 \text{ Kg/h}$

Air inlet 1/4 "
Air working pressure 7 bar

Encumbrance 650 X 980 mm

Net weight 75 Gross weight 110

Overall dimensions 1480x830x950 mm

Primus Belgium Driemasten 126 B-8560 Gullegem Belgium Tel.: +32(0)56 43 52 00 Fax: +32(0)56 40 34 63 E-mail: info@primuslaundry.com

Primus CE Mistecka 1116 742 58 Pribor Czech Republic Tel.: +420 556 768 800 Fax: +420 556 723 383 E-mail: sales@primuslaundry.cz